

SNAP FRAMES

OPERATING INSTRUCTIONS

GRAPHIC REPLACEMENT

1. Turn off power
2. Open the four upper covers
3. Remove front board and AD graphic
4. Change AD graphic
5. Place the front board
6. Close the four upper cover

ON THE WALL

1. Measure installation dimension
2. Fix the light box on the wall by screws
 - a.) If the wall is made of wood, plastic, aluminum and so on, you can directly fix the light box on the wall by self-tapping screws.
 - b.) If the wall is made of concrete, brick, marble and so on, you should firstly drill holes in the wall and screw expand screws, and then fix the light box.
3. Connect the power supply



WARNING

This product is not waterproof. To prevent a fire or shock hazard, do not place any container with liquid near this equipment or expose it to dripping, splashing, rain or moisture.

SAFETY INSTRUCTIONS

To ensure your personal safety and to maximize the full operating potential of your Drive, read and follow these safety precautions:

ENVIRONMENT- DO NOT use the unit at places with high levels of dust, high temperature, or high humidity. Please use the unit in a place where it is not subjected to vibrations or shocks.

POWER- Please use correct power as required for this product.

READ INSTRUCTIONS- Read all safety and operating instructions before the Drive is operated.

RETAIN INSTRUCTIONS- Retain the safety and operating instructions for future reference.

FOLLOW INSTRUCTIONS- Follow all operating and use instructions.

HEED WARNINGS- All warnings must be adhered to.

CLEANING- DO NOT use liquid, aerosol cleaners, or alcohol. Use only a damp cloth to clean the exterior housing.

WATER AND MOISTURE- DO NOT use this product near water.

POWER SOURCES- Operate this product from the type of power source indicated on the marking label.

OVERLOADING- DO NOT overload wall outlets and extension cords. Doing so can result in fire or electric shock.

OBJECT AND LIQUID ENTRY- Never push objects of any kind into this product. Touching dangerous voltage points may cause a short resulting in fire or electric shock. Do not spill liquid of any kind on this product.

CONDENSATION- Moisture will form in the operating section of the product causing performance to be impaired if it is brought from cool surroundings into a warmer environment. If you are moving the unit to a location with a warmer temperature, let the product stand for 1 to 2 hours in the new location before turning it back on.